

Name of Driver		Date	Track		Engine	Plug		Muffler	
Reno Savoya		11/07/2021	IBC Barcelos Condition: 25°C, very high grip		Picco P3TT	Picco P5TH		EFRA 2166	
Spur Gear	Clutch Bell	Clutch Spring		Clutch Shoe	Tire	Tire Insert	Wheel	Body	Fuel
46 T	☐ Std. ☒ LW 13 T	☐ 0.90 ☒ 1.00 ☐ 0.95 ☐ 1.10	Carbon ☒ Aluminum ☒ 3	Tire : AKA Catapult Compounds: SLW	AKA	Stock	TKI2	Hot Road G	

● Diff. Gear Set-Up

	Front	Center	Rear
Diff. Gear	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD	☒ 10/20 ☐ 12/18 ☐ LSD
Ring Gear	☒ 43/13 ☐ 42/12	# 30k	☒ 43/13 ☐ 42/12
	# 30k	# 50k	# 30k

● Shock Set-Up

	Front	Rear
Shock Type	P : w/Diaphragm A : Aeration	Size 47mm - type P
Shock Piston	B : Black W : White T : Taper	Size 55mm - type P
Shock Oil	# 650	# 750
Shock Spring	Red 70mm	Red 81mm

● Ride Height

Front	Rear
22 mm	27 mm

● Rebound

Front	Rear
102 mm	119 mm

● Camber Angle

Front	Rear
+ 2°	+ 3°


● Toe Angle

Front	Rear
+ 2°	☒ 2.5° ☐ 3° ☐ 3.5°

● Wheelbase

Collar of Rear Hub	Front Side 5 mm Rear Side 0 mm
--------------------	-----------------------------------

● Shock Mount Position



Shock Stay

Front	☐ Short ☒ Long
Rear	☐ Short ☒ Long


Rear Upper Shock Bush

☐ Std. ☒ Long
--

Sus. Arm

Front	☐ In ☒ Out
Rear	☐ In ☒ Out

● Rear Upper Arm Position



● Rear Wheel Hub

☐ Narrow ☒ Std. ☐ Wide
--

☐ Plastic ☒ Aluminum
--

Hub Carrier Bush

☒ Plastic ☐ Brass

☐ ☐ ☒ ☐
☐ ☐ ☐ ☐


● Front Sus. Arm

☒ Soft (Std.) ☐ Hard

● Front Sus. Bush

Rear Side	☐ ☐ ☒ ☐
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

☒ Narrow ☐ Std. ☐ Wide
--

● Front Hub Carrier

☐ Plastic ☒ Aluminum
☐ 13° ☐ 16° ☐ 17.5° ☐ 19°



Lower Bush

☒ Plastic ☐ Brass
☐ -1° ☐ 0° ☐ +1°

● Rear Sus. Bush

Front Side	☒ ☐ ☐ ☐
Rear Side	☒ ☐ ☐ ☐ ☐ ☐ ☐ ☐


● Rear Sus. Arm

☐ Soft (Std.) ☒ Hard
Rear Sus. Bush
☐ Short ☐ Medium ☒ Long

● Servo Horn

Steering	Throttle
☐ Plastic ☒ AL. Long ☐ AL. Short	☐ Plastic ☒ AL.

● Steering Plate



● Sway Bar



Front	Rear
φ 2,7mm	φ 2,5mm
1 mm	1 mm

● Weight

Front	Rear
☐ None ☐ IFW604-10 ☒ IFW604-20 ☐ other	☐ None ☐ IFW605-10 ☒ IFW605-20 ☐ other

● Wing

☒ IF491(TKI4)	Flap ☒ None ☐ 5mm ☐ 8mm ☒ Holes
---	--

memo:

Options:
IFW629 22 degrees aluminum caster blocks
IFW612
Titanium screws and turnbuckles for weight saving
IFW426 Aluminum AMB plate
IFW616, MA081, IFW617 dogbone driveshafts for center
IFW613 front CVA
IFW450 aluminum servo saver